17" (16.0" VIS) XSD™ monitor

107E56

- *17-inch (16.0" VIS) color monitor with excellent front of screen performance for use with MACs and PCs*
- *Autoscan covers horizontal frequencies up to 70 kHz offering a maximum resolution of 1280 x 1024 with flicker free display of 1024 x 768 at up to 88 Hz*
- *Flat square High Contrast CRT with high-resolution 0.27 mm dot pitch (0.23 hdp)*
- *XSD-Xtra Space Design for large screen display in a small footprint: World's shortest 17-inch conventional monitor with maximum depth of only 419 mm/16.5"*
- *Multimedia Base option*

Optional Multimedia Base (6G3B12)

All accessories might not available in all market. Please check with your local philips representative for availability.

PHILIPS

17" (16.0" VIS) XSD™ monitor

Technical Specifications

CRT panel

• Size (inch/cm)	17"/ 41 cm
• Deflection angle (degrees)	90°
• Dot pitch	0.27 mm
• Horizontal pitch	0.23 mm
-Tube type	Shadow mask, Flat Square, High Contrast, Anti Glare, Anti Static, Anti reflection, Light Transmission 47%
• Phosphor	P22
• Recom. display area(mm)	306 x 230 mm
• Recom. display area(inch)	12.0" x 9.0"
• Max. display area(mm)	327 x 245 mm
• Max. display area(inch)	12.9" x 9.7"

Scanning

• Horizontal scanning	30 - 70 kHz
• Vertical scanning	50 - 160 Hz

Video

• Video dot rate	120 MHz
• Input impedance	
-Video	75 Ohm
-Sync	2.2k Ohm
• Input signal levels	0.7 Vpp
• Sync input signal	Separate sync
	Composite sync
• Sync polarities	Positive and negative

White color temperature

Chromaticity CIE coordinates

• at 9300 K:	x=0.283, y=0.297
• at 6500 K:	x=0.313, y=0.329

Resolution & preset modes

• Max. resolution	1280 x 1024
• Recom. resolution	1024 x 768
• 8 user definable modes	
• 14 factory preset modes	

	H.freq (KHz)	V.freq (Hz)
640 x 350	31.5K	70
640 x 350	37.9K	85
640 x 480	37.9K	72
640 x 480	37.5K	75
640 x 480	50.6K	100
720 x 400	37.9K	85
800 x 600	37.9K	60
800 x 600	48.1K	72
800 x 600	63.9K	100
832 x 624	49.7K	75
1024 x 768	48.4K	60
1024 x 768	56.5K	70
1152 x 864	67.5K	75
1280 x 1024	64.0K	60

Plug and play compatibility

- Display Data Channel DDC 2B (VESA)
- Microsoft® Windows® 95/98/Me & 2000/NT/XP compatible
- sRGB

Power management

Complies with EPA Energy Star and NUTEK specifications

• Operation	64 W (typical)
• Off mode/Deep Sleep	< 1 W

Low-emission characteristics

- Complies with MPR-II specifications

Monitor controls and functions

• Main	3-button OSD
	Brightness +/- direct access
	Contrast+/- direct access
• On Screen Display	Language (English, Spanish, French, German, Italian, Chinese, Portuguese, Korean), zoom, horizontal, vertical, pincushion, balanced, trapezoid, parallelogram, color, reset, degauss, moire, serial number, resolution, frequency, sRGB

Connections and cables

• Connections	
- Video	15-pin D-sub (analog)
• Cables	D-Sub Video cable(fixed), power cord

Regulatory approvals

- MPR-II Low Emission
- TÜV/GS, TÜV/Ergo
- FCC-B, UL, CSA, DHHS
- SEMKO, Poland-B sign, C-Tick
- CE, BSMI, PSB
- NUTEK, Energy Star

Physical specifications

• Dim. incl. base (WxHxD)	397 x 383 x 419 mm
• Dim. incl. base (WxHxD)	15.6" x 15.1" x 16.5" inch
• Dim. excl. base (WxHxD)	397 x 333 x 419 mm
• Dim. excl. base (WxHxD)	15.6" x 13.1" x 16.5" inch
• Weight	14.5 kg
• Power supply	Please refer to rating label
• Temperature (operational)	0°C to 40°C/ 32°F to 104° F
• Temperature (storage)	-25°C to 65°C/ -13°F to 149°F
• Relative humidity	5% to 95%
• MTBF	> 75,000 H

Other

- Multimedia Base option type: 6G3B12

As an Energy Star partner, Philips has determined that this product meets the Energy Star guidelines for energy efficiency.
Microsoft and Windows are registered trademarks of Microsoft Corporation
MacOS is a registered trademark of Apple Computer, Inc.

All data subject to change without notice
Release date: January 2004
www.philips.com

PHILIPS